

*Product design features:*

- 12+ years design life, EUROBAT specification Long Life
- Extremely high cyclic life and float life performance
- Wide range of operating temperature -20°C to +55°C
- One-way valve regulated system with flame-arrestor
- Internal gas recombination efficiency 98% - 99%
- Easy for installation, maintenance free product
- Delivered ready for use at 100% of its nominal capacity
- Shock resistant ABS flame retardant container and lid
- Three-layer terminal sealing for leak-free operation
- Female M8 brass terminals with no need for retightening
- Non-hazardous cargo for ground, sea and air transport
- Fully recyclable product



**Electrical Characteristics**

	at 20°C	at 25°C
Nominal voltage	12 Volts	
10 hour capacity to 1.80 Vpc	158.0 Ah	163.0 Ah
8 hour capacity to 1.75 Vpc	152.8 Ah	157.6 Ah
Float voltage	2.27 Vpc ± 1%	2.26 Vpc ± 1%
Accelerated charge voltage	2.40 Vpc without current limit	
Shelf life	1 year	
Short circuit current	2830 Amps	
Internal resistance	4.3 mΩ	

MONBAT is proud to be certified for ISO 9001:2000,  
ISO 14001:1996, OHSAS 18001:1999, AQAP 2110

**Mechanical Characteristics**

	SI Units	US Units
Length	555 mm	21.8 inches
Width	125 mm	4.9 inches
Height	324 mm	12.8 inches
Weight	60.0 kg	132.3 lbs
Terminal Torque	9.0 Nm	79.6 in.lbs

All MONBAT VRLA batteries are fully  
compliant with IEC 60 896 - 21/22,  
EN 60 896 - part 2, BS 6290 - part 4

**Discharge performance at constant current discharge (A) for battery 12MVR150 at 20°C**

Uf, Vpc	5 min	10 min	15 min	20 min	30 min	45 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h	20 h
1.60	430.8	311.2	240.0	202.3	156.4	123.0	101.7	59.3	43.2	33.7	28.4	19.7	16.4	9.3
1.65	407.6	295.6	231.9	196.8	153.4	119.5	100.0	58.7	42.6	33.4	28.3	19.5	16.3	9.2
1.70	380.0	278.5	222.8	191.9	149.2	117.4	98.4	57.9	42.0	33.0	27.8	19.3	16.2	9.1
1.75	336.6	251.8	211.4	183.0	143.6	115.2	96.6	57.3	41.5	32.7	27.5	19.1	15.9	9.0
1.80	293.8	226.4	195.5	168.9	135.2	110.7	93.5	55.7	40.6	32.0	27.1	18.9	15.8	8.8
1.85	235.0	198.6	175.0	150.5	123.0	102.4	85.8	53.0	38.9	31.0	26.3	18.3	15.3	8.4

**Discharge performance at constant current discharge (A) for battery 12MVR150 at 25°C**

Uf, Vpc	5 min	10 min	15 min	20 min	30 min	45 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h	20 h
1.60	443.7	320.5	247.2	208.4	161.1	126.7	104.7	61.1	44.5	34.8	29.2	20.2	16.9	9.6
1.65	419.8	304.5	238.9	202.7	158.0	123.0	103.0	60.5	43.9	34.4	29.1	20.1	16.8	9.4
1.70	391.4	286.9	229.5	197.7	153.7	120.9	101.4	59.6	43.3	34.0	28.7	19.9	16.6	9.3
1.75	346.7	259.4	217.7	188.5	147.9	118.7	99.5	59.0	42.7	33.6	28.3	19.7	16.4	9.2
1.80	302.6	233.2	201.4	174.0	139.3	114.1	96.3	57.4	41.8	33.0	27.9	19.5	16.3	9.1
1.85	242.1	204.6	180.3	155.0	126.7	105.5	88.4	54.6	40.0	31.9	27.1	18.9	15.7	8.7

**Discharge performance at constant power discharge (W per cell) for battery 12MVR150 at 20°C**

Uf, Vpc	5 min	10 min	15 min	20 min	30 min	45 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h	20 h
1.60	859.2	634.2	519.0	433.2	331.2	245.6	199.2	114.0	86.8	69.7	57.2	38.8	32.2	18.1
1.65	813.0	615.0	504.0	420.0	324.8	241.2	196.8	113.3	86.2	69.3	57.0	38.6	32.1	18.0
1.70	747.0	585.0	481.5	409.6	318.4	239.2	195.5	112.2	85.5	68.5	56.5	38.3	31.9	17.9
1.75	679.5	540.8	450.0	388.5	307.2	234.8	191.8	111.0	84.3	67.9	56.0	38.0	31.7	17.8
1.80	603.0	492.0	414.8	361.7	290.4	225.6	186.0	108.5	82.9	66.5	54.8	37.5	31.2	17.5
1.85	505.0	418.5	366.7	325.0	263.6	210.0	173.0	103.7	80.4	64.2	53.0	36.2	30.4	17.0

**Discharge performance at constant power discharge (W per cell) for battery 12MVR150 at 25°C**

Uf, Vpc	5 min	10 min	15 min	20 min	30 min	45 min	1 h	2 h	3 h	4 h	5 h	8 h	10 h	20 h
1.60	884.9	653.2	534.6	446.2	341.1	253.0	205.1	117.4	89.4	71.8	58.9	40.0	33.2	18.6
1.65	837.4	633.5	519.1	432.6	334.5	248.4	202.7	116.7	88.8	71.4	58.7	39.8	33.0	18.5
1.70	769.4	602.6	495.9	421.9	328.0	246.4	201.4	115.5	88.1	70.6	58.2	39.4	32.9	18.4
1.75	699.9	557.0	463.5	400.2	316.4	241.8	197.6	114.3	86.8	69.9	57.7	39.1	32.7	18.3
1.80	621.1	506.8	427.2	372.5	299.1	232.4	191.6	111.8	85.4	68.5	56.4	38.6	32.1	18.0
1.85	520.2	431.1	377.7	334.8	271.5	216.3	178.2	106.8	82.8	66.1	54.6	37.3	31.3	17.5