

MONBAT Premium SMF NP56L1X0_1 56 Ah

According to EN 50342



Premium

SEALED MAINTENANCE FREE



Electrical specification

Voltage:	12V
Capacity C²⁰:	56 Ah
Cold cranking current:	560 A [EN]
Cold cranking current:	340 A [DIN]

Mechanical specification

Dimensional group:	L1
ETN reference:	556 112 056 SMF
DIN reference:	55612
Dimensions^A in mm (LxWxH):	207x175x190
Cell Layout:	0
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B13
	Colour	Grey

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Grey

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Grey

Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Grey


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V2	E2


Weight^B

Battery weight in kg:	10.30
Acid weight in kg:	3.70
Total battery weight in kg:	14.00

Layout



Hold-down



Separator

Type	PE
-------------	-----------

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.