

MONBAT Premium ASIA NP66J6X0_1 65 Ah

According to EN 50342 / JIS D 5301



Premium

SEALED MAINTENANCE FREE



Electrical specification

Voltage:	12V
Capacity C²⁰:	65 Ah
Cold cranking current:	600 A [EN]
Cold cranking current:	360 A [DIN]

Mechanical specification

Dimensional group:	D23
ETN reference:	565 028 060 SMF
DIN reference:	-
Dimensions^A in mm (LxWxH):	230x170x220
Cell Layout:	1
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B1
	Colour	Grey

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Grey

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Grey

Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Grey


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V2	E2

Weight^B

Battery weight in kg:	11.10
Acid weight in kg:	4.80
Total battery weight in kg:	15.90

Layout



Hold-down



Separator

Type	PE
-------------	-----------

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.