

MONBAT SLI SHD G89R31XT0_1 105 Ah

According to EN 50342


Electrical specification

Voltage:	12V
Capacity C ²⁰ :	105Ah
Cold cranking current:	800 A [EN]
Cold cranking current:	850 A [SAE]

Mechanical specification

Dimensional group:	GR31
ETN reference:	605 103 080
DIN reference:	60502
Dimensions ^A in mm (LxWxH):	336x173x235
Cell Layout:	9
Terminal Type:	8

Container

Case	Material	Polypropylene
	Bottom hold-down	B0
	Colour	Grey

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Grey

Vent caps	Material	Polypropylene
	Type	Integrated
	Colour	Grey


Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Grey

Battery classification as per EN 50342-1

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V2	E2

Weight^B

Battery weight in kg:	16.80
Acid weight in kg:	8.20
Total battery weight in kg:	25.00

Layout

Hold-down

Separator

Type	PE
------	----

^{A.} Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.

^{B.} Weight may vary ±5%.

- A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
- B. Weight may vary $\pm 5\%$.