

**START EFB PREMIUM G166J6X0\_1 65 Ah**

According to EN 50342


**EFB**  
PREMIUM

**Electrical specification**

|                            |             |
|----------------------------|-------------|
| Voltage:                   | 12V         |
| Capacity C <sup>20</sup> : | 65 Ah       |
| Cold cranking current:     | 560 A [EN]  |
| Cold cranking current:     | 580 A [SAE] |

**Mechanical specification**

|                                        |             |
|----------------------------------------|-------------|
| Dimensional group:                     | D23         |
| ETN reference:                         | 565 003 056 |
| DIN reference:                         | 56503       |
| Dimensions <sup>A</sup> in mm (LxWxH): | 230x170x220 |
| Cell Layout:                           | 1           |
| Terminal Type:                         | 1           |

**Container**

|      |                  |               |
|------|------------------|---------------|
| Case | Material         | Polypropylene |
|      | Bottom hold-down | B1            |
|      | Colour           | Grey          |

|     |              |               |
|-----|--------------|---------------|
| Lid | Material     | Polypropylene |
|     | Cover design | SMF           |
|     | Colour       | Grey          |

|           |          |               |
|-----------|----------|---------------|
| Vent caps | Material | Polypropylene |
|           | Type     | SMF           |
|           | Colour   | Grey          |



|         |          |               |
|---------|----------|---------------|
| Handles | Material | Polypropylene |
|         | Position | Top - on lid  |
|         | Colour   | Grey          |

**Battery classification as per EN 50342-6**

| Water consumption | Charge retention | Vibration resistance | Endurance Level | Micro-cycle performance |
|-------------------|------------------|----------------------|-----------------|-------------------------|
| W4                | C2               | V2                   | E2              | M2                      |

**Weight<sup>B</sup>**

|                             |       |
|-----------------------------|-------|
| Battery weight in kg:       | 11.80 |
| Acid weight in kg:          | 5.10  |
| Total battery weight in kg: | 16.90 |

**Layout**

**Hold-down**

**Separator**

|      |    |
|------|----|
| Type | PE |
|------|----|

<sup>A.</sup> Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.

<sup>B.</sup> Weight may vary ±5%.