

START SLI EN A66B2W0_1 60 Ah

According to EN 50342


SLI
Electrical specification

Voltage:	12V
Capacity C ²⁰ :	60 Ah
Cold cranking current:	540 A [EN]
Cold cranking current:	560 A [SAE]

Mechanical specification

Dimensional group:	LB2
ETN reference:	560 076 054 SMF
DIN reference:	56076
Dimensions ^A in mm (LxWxH):	242x175x175
Cell Layout:	1
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B4
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black



Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Black

Battery classification as per EN 50342-1

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V2	E1

Weight^B

Battery weight in kg:	9.85
Acid weight in kg:	4.35
Total battery weight in kg:	14.20

Layout

Hold-down

Separator

Type	PE
------	-----------

^{A.} Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.

^{B.} Weight may vary ±5%.