MONBAT BATTERIES

DATA SHEET

Date of update: 01.04.2026

START SLI PREMIUM JIS NP66J6X0_1 65 Ah

According to EN 50342



SLI PREMIUM

Electrical specification

Voltage:	**12V**
Capacity C^{20}:	**65 Ah**
Cold cranking current:	**600 A [EN]**
Cold cranking current:	**620 A [DIN]**

Mechanical specification

Dimensional group:	**D23**
ETN reference:	**565 028 060 SMF**
DIN reference:	**56528**
Dimensions[A] in mm (LxWxH):	**230x170x220**
Cell Layout:	**1**
Terminal Type:	**1**

Container

Case	**Material**	**Polypropylene**
	Bottom hold-down	**B1**
	Colour	**Grey**

Lid	**Material**	**Polypropylene**
	Cover design	**SMF**
	Colour	**Grey**

Vent caps	**Material**	**Polypropylene**
	Type	**SMF**
	Colour	**Grey**

Handles	**Material**	**Polypropylene**
	Position	**Top - on lid**
	Colour	**Grey**

Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	**C2**	**V2**	**E2**

Weight[B]

Battery weight in kg:	**11.10**
Acid weight in kg:	**4.90**
Total battery weight in kg:	**16.00**

Layout



Hold-down



Separator

Type	**PE**

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.