



DEEP CYCLE
PROFESSIONAL

6V EU J305 DC-350 Ah (C₂₀)



PHYSICAL CHARACTERISTICS		
	SI Units	US Units
Length	311 mm	12,25 inch
Width	180 mm	7,09 inch
Height	356 mm	14,02 inch
Typical weight	47.15 kg	103.95 lbs

Specifications:

- Nominal voltage: 6 V
- Rated capacity: 350 Ah (at C₂₀ and 25 °C)
- Plate technology: Antimony / Antimony
- Separator: Polyethylene + glass mat
- Electrolyte: Sulphuric acid (SG 1,28) OCV 6.35V
- Standards: IEC 60254; IEC 61427
- Case / Lid material: Polypropylene
- Lid type: Flat
- Terminal type: Conical
- Carrying Handles: Available
- Cycles at 50% DoD: up to 900 cycles
- PVES applications: up to 2000 cycles

Performance characteristics:



BATTERY DISCHARGE PERFORMANCE AT 25°C							
Discharge rate	C ₅ (5 h)	C ₂₀ (20 h)	C ₁₀₀ (100 h)	Capacity at 25 A			
End of discharge voltage	5,10 V	5,25 V	5,40 V	5,25 V			
Discharge capacity	287 Ah	350 Ah	385 Ah	790 min			
Temperature correction factor of discharge C ₅ (5 h) capacity							
Temperature	-10 °C	0 °C	20 °C	25 °C	30 °C	35 °C	40 °C
Correction factor	0.80	0.88	0.98	1.00	1.03	1.05	1.07

BATTERY CHARGE CONDITIONS AT 25°C	
Charging profile:	Charge factor: 1.10 – 1.20
I _U I _a –characteristics for flooded batteries	Charging times with I _U I _a -characteristics in hours at 25 °C
<p>Stage1: Constant current Stage 2: Constant voltage Stage 3: Constant current</p>	

It is mandatory to check the electrolyte level every 3 months and top up with deionized water to the markings.

BATTERY DISCHARGE CURVES AT 25°C

DISCHARGE PERFORMANCE AT CONSTANT CURRENT DISCHARGE (A)



It is mandatory to check the electrolyte level every 3 months and top up with deionized water to the markings.