

MONBAT Formula ASIA KX45J4X0_1 45 Ah

According to EN 50342 / JIS D 5301



Formula Asia

JIS SEALED MAINTENANCE FREE



Electrical specification

Voltage:	12V
Capacity C²⁰:	45 Ah
Cold cranking current:	330 A [EN]
Cold cranking current:	200 A [DIN]

Mechanical specification

Dimensional group:	NS60
ETN reference:	545 051 033 SMF
DIN reference:	-
Dimensions^A in mm (LxWxH):	237x128x220
Cell Layout:	1
Terminal Type:	3

Container

Case	Material	Polypropylene
	Bottom hold-down	B0
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black

Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Black


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V1	E1

Weight^B

Battery weight in kg:	7.60
Acid weight in kg:	4.00
Total battery weight in kg:	11.60

Layout



Hold-down



Separator

Type	PE
-------------	-----------

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.