

START Extra A44B1W0_1 40 Ah

According to EN 50342



Electrical specification

Voltage:	12V
Capacity C²⁰:	40 Ah
Cold cranking current:	320 A [EN]
Cold cranking current:	190 A [DIN]

Mechanical specification

Dimensional group:	LB1
ETN reference:	540 046 032 SMF
DIN reference:	54046
Dimensions^A in mm (LxWxH)	207x175x175
Cell Layout:	0
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B4
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black

Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Black


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W3	C2	V1	E1


Weight^B

Battery weight in kg:	7.20
Acid weight in kg:	3.80
Total battery weight in kg:	11.00

Layout



Hold-down



Separator

Type	PE
-------------	-----------

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.