

START Mega A56B2P0_1 55 Ah

According to EN 50342



Electrical specification

Voltage:	12V
Capacity C²⁰:	55 Ah
Cold cranking current:	480 A [EN]
Cold cranking current:	280 A [DIN]

Mechanical specification

Dimensional group:	LB2
ETN reference:	555 019 048 SMF
DIN reference:	55519
Dimensions^A in mm (LxWxH)	242x175x175
Cell Layout:	0
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B4
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black

Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Black


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V1	E1


Weight^B

Battery weight in kg:	9.20
Acid weight in kg:	4.40
Total battery weight in kg:	13.60

Layout



Hold-down



Separator

Type	PE
-------------	-----------

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.