

MONBAT SLI SHD E990BX5_1 150 Ah

According to EN 50342



Electrical specification

Voltage:	12V
Capacity C ²⁰ :	150 Ah
Cold cranking current:	850 A [EN]
Cold cranking current:	900 A [SAE]

Mechanical specification

Dimensional group:	B
ETN reference:	650 104 085
DIN reference:	65004
Dimensions ^A in mm (LxWxH):	513x223x223
Cell Layout:	3
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B0
	Colour	Grey

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Grey

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Grey

Handles	Material	Polypropylene
	Position	Sides - on container
	Colour	Black


Battery classification as per EN 50342-1

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V2	E2

Weight^B

Battery weight in kg:	25.90
Acid weight in kg:	14.70
Total battery weight in kg:	40.60

Layout



Hold-down



Separator

Type	PE with Glass Mat
------	-------------------

- ^{A.} Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
^{B.} Weight may vary ±5%.