MONBAT BATTERIES

DATA SHEET

Date of update: 01.04.2026

MONBAT AGM PREMIUM GP67L2K3_1 60 Ah

According to EN 50342



Electrical specification

Voltage:	**12V**
Capacity C^{20}:	**60 Ah**
Cold cranking current:	**640 A [EN]**
Cold cranking current:	**660 A [SAE]**

Mechanical specification

Dimensional group:	**L2**
ETN reference:	**560 901 064**
DIN reference:	**56001**
Dimensions[A] in mm (LxWxH):	**242x175x190**
Cell Layout:	**0**
Terminal Type:	**1**

Container

Case	**Material**	**Polypropylene**
	Bottom hold-down	**B13**
	Colour	**Grey**

Lid	**Material**	**Polypropylene**
	Cover design	**KAMINA**
	Colour	**Grey**

Vent caps	**Material**	**Polypropylene**
	Type	**KAMINA**
	Colour	**Grey**

Handles	**Material**	**Polypropylene**
	Position	**Top - on lid**
	Colour	**Grey**

Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level	Micro-cycle performance
W5	**C2**	**V3**	**E3**	**M3**

Weight[B]

Battery weight in kg:	**14.70**
Acid weight in kg:	**3.45**
Total battery weight in kg:	**18.15**

Layout



Hold-down



Separator

Type	**AGM**

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.